TEMPOMATIC 4 electronic tap

Ref. 443426

Integrated batteries

DESCRIPTION

TEMPOMATIC 4 electronic tap - Ref. 443426

Electronic basin tap for panels:
Battery-operated with integrated 123 6V Lithium batteries.
Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
Scale-resistant flow straightener.
Duty flush (~60 seconds every 24 hours after last use).
Presence detection sensor at the end of the spout optimises presence detection.
Chrome-plated stainless steel body L. 130mm.
Cap fixed in place by 2 concealed screws.
Installation for panels from 1 - 24mm.
Anti-blocking security.
Stopcock.
Suitable for people with reduced mobility.
30-year warranty.

ADVANTAGES

- Exceptional water savings: 90%
- Hygiene: no manual contact
- Integrated electronics
- Replace batteries without removing tap

TECHNICAL CHARACTERISTICS

TEMPOMATIC 4 electronic tap - Ref. 443426

Supply	6V batteries
Connector	M1/2"
Technology	Electronic
Spout length	130mm
Flow rate	3 lpm
Norms	ACS SVGW
Warranty	30 YEAR WARRANTY