

## BIOCLIP mechanical basin mixer

Ref. 2821T

Single hole mechanical removable mixer H. 95mm L. 120mm, solid lever



### DESCRIPTION

**BIOCLIP mechanical basin mixer - Ref. 2821T**





Deck-mounted mechanical basin mixer.  
 BIOCLIP mechanical mixer: mixer can be removed entirely for cleaning and disinfection.  
 Single hole mixer with spout H. 95mm L. 120mm fitted with a BIOSAFE hygienic flow straightener.  
 Spout suitable for fitting a BIOFIL point-of-use filter.  
 Ø 35mm ceramic cartridge with pre-set maximum temperature limiter.  
 Thermal shocks are possible without removing the control lever or shutting off the cold water supply.  
 Body and spout with smooth interiors and low water volume.  
 Flow rate limited to 5 lpm at 3 bar.  
 Solid control lever.  
 Without pop-up waste.  
 PEX flexibles F3/8" supplied with stopcocks in chrome-plated brass.  
 Fixing reinforced via 2 stainless steel rods.  
 Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.  
 Single hole mixer suitable for people with reduced mobility.  
 Mixer with 30-year warranty.  
 Also available with copper tubes.

### TECHNICAL CHARACTERISTICS

**BIOCLIP mechanical basin mixer - Ref. 2821T**

Connector	F3/8"
Technology	BIOCLIP removable mixer
Drop height	95mm
Spout length	120mm
Flow rate	5 lpm at 3 bar
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	ACS WWRAS
Warranty	30 YEAR WARRANTY
Repairability	50 YEARS REPAIRABILITY

### ADVANTAGES

-  Hygiene: remove for internal cleaning
-  Hygiene: smooth interior reduces bacteria
-  Pre-set maximum temperature limiter
-  Ergonomic: solid lever is easy to grip

