

# SECURITHERM thermostatic sink mixer

Ref. H9716

Single hole dual control tall mixer H. 225mm L. 200mm





## DESCRIPTION

### SECURITHERM thermostatic sink mixer - Ref. H9716

Deck-mounted SECURITHERM thermostatic dual control sink mixer.  
 Tall, single hole mixer with swivelling tubular spout H. 225mm L.200mm with smooth interior.  
 Spout with hygienic flow straightener, suitable for fitting a BIOFIL terminal filter.  
 Anti-scalding failsafe: immediate shut-off if cold or hot water supply fails.  
 Scale-resistant thermostatic cartridge for adjusting the temperature.  
 ¼-turn ceramic head for adjusting the flow rate.  
 Temperature can be adjusted, with two temperature limiters: first temperature limiter set at 38°C (can be overridden), and second temperature limiter set at 41°C.  
 Thermal shocks are easy to undertake without removing the control knob or shutting off the cold water.  
 Flow rate limited to 9 lpm at 3 bar.  
 ERGO control knobs.  
 PEX flexibles F3/8" with filters and non-return valves.  
 Fixing reinforced by 2 stainless steel rods.  
 Thermostatic mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.  
 Suitable for people with reduced mobility.  
 30-year warranty.







## ADVANTAGES

-  SECURITHERM: Optimum anti-scalding safety
-  Hygiene: smooth interior reduces bacteria
-  Thermostatic: complete temperature stability
-  Thermal shock possible without removing the lever

## TECHNICAL CHARACTERISTICS

### SECURITHERM thermostatic sink mixer - Ref. H9716

Connector	F3/8"
Technology	SECURITHERM thermostatic mixer
Drop height	225mm
Spout length	200mm
Flow rate	9 lpm at 3 bar
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	   
Warranty	