

SECURITHERM EP pressure-balancing basin mixer

Ref. 2721LEP

Single hole mechanical mixer H. 95mm L. 120mm



DESCRIPTION

SECURITHERM EP pressure-balancing basin mixer - Ref. 2721LEP

Deck-mounted mechanical basin mixer with pressure-balancing. Single hole mixer with curved spout H. 95mm L. 120mm fitted with a hygienic BIOSAFE outlet.

Spout suitable for fitting a BIOFIL point-of-use filter.

Ø 35mm ceramic cartridge with pressure-balancing and pre-set maximum temperature limiter.

Anti-scalding safety: HW flow rate is reduced if CW supply fails (and vice versa).

Stable temperature regardless of variations in pressure and flow rate in the system.

Body and spout with smooth interiors (reduced bacterial development)

Thermal shocks are easy to undertake without removing the control lever or shutting off the water supply.

Flow rate limited to 5 lpm at 3 bar.

Hygiene control lever L. 150mm.

Without pop-up waste.

F3/8" PEX flexibles with filters and non-return valves.

Fixing reinforced via 2 stainless steel rods.

Mechanical mixer with SECURITHERM EP pressure-balancing ideal for healthcare facilities, retirement and care homes, hospitals and clinics.






Single hole mixer suitable for people with reduced mobility.

Mixer with 30-year warranty.

Also available with copper tails.

TECHNICAL CHARACTERISTICS

SECURITHERM EP pressure-balancing basin mixer - Ref. 2721LEP

Connector	F3/8"
Technology	SECURITHERM EP mechanical mixer
Drop height	95mm
Spout length	120mm
Flow rate	5 lpm at 3 bar
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	ACS    
Warranty	

ADVANTAGES



HW flow rate reduced if CW supply fails



EP: reduces temperature variations



Hygiene: smooth interior reduces bacteria



Thermal shocks are possible without removing lever

