

Mechanical sink mixer

Ref. 2506T2

Single hole mechanical mixer with swivelling spout H. 220mm L. 200mm





DESCRIPTION

Mechanical sink mixer - Ref. 2506T2

Deck-mounted mechanical sink mixer.
 Single hole mechanical sink mixer with swivelling, tubular spout H. 220mm L. 200mm fitted with a hygienic flow straightener suitable for fitting a BIOFIL point-of-use filter.
 Ø 35mm ceramic cartridge with maximum temperature limiter supplied but not installed.
 Spout with smooth interior.
 Flow rate limited to 9 lpm at 3 bar.
 Slimline control lever.
 Without pop-up waste.
 F3/8" PEX flexibles.
 Fixing reinforced by 2 stainless steel rods.
 Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
 Single hole mixer suitable for people with reduced mobility.
 30-year warranty.





TECHNICAL CHARACTERISTICS

Mechanical sink mixer - Ref. 2506T2

| | |
|---------------------|---|
| Connector | F3/8" |
| Drop height | 220mm |
| Spout length | 200mm |
| Flow rate | 9 lpm at 3 bar |
| Temperature limiter | Yes |
| Finish | Chrome-plated brass |
| Norms | ACS   |
| Warranty |  |
| Repairability |  |



ADVANTAGES

-  Hygiene: smooth interior reduces bacteria
-  Hygiene: hygienic flow straightener with no grid
-  Ergonomic: slimline lever is easy to grip
-  Comfort: optimum drop height and spout projection

