

# SECURITHERM thermostatic shower mixer



Ref. H9739





Dual control thermostatic shower mixer

## DESCRIPTION

### SECURITHERM thermostatic shower mixer - Ref. H9739





SECURITHERM dual control thermostatic shower mixer:  
 Mixer with anti-scalding safety: shuts off automatically if cold water supply fails.  
 Prevents cold showers: shuts off automatically if hot water supply fails.  
 Scale-resistant thermostatic cartridge for temperature adjustment.  
 1/4-turn ceramic head for flow rate adjustment.  
 Temperature control from 25 - 40°C with maximum temperature limiter set at 38°C.  
 Thermal shocks are possible without removing the control knob or shutting off the cold water.  
 Flow rate regulated at 9 lpm.  
 Chrome-plated brass body and CLASSIC controls.  
 M1/2" shower outlet.  
 Filters and non-return valves F3/4" integrated on the inlets.  
 Mixer with offset STOP/CHECK wall connectors, M1/2" M3/4".  
 Ideal for healthcare facilities, retirement and care homes, hospitals and clinics.  
 Mixer suitable for people with reduced mobility.  
 Shower mixer with 30-year warranty.

## ADVANTAGES

-  SECURITHERM: Optimum anti-scalding safety
-  Pre-set maximum temperature limiter
-  Thermostatic: total temperature stability
-  Ergonomic: controls are easy to grip

## TECHNICAL CHARACTERISTICS

### SECURITHERM thermostatic shower mixer - Ref. H9739

Connector	M1/2"
Technology	SECURITHERM thermostatic dual control mixer
Length	81mm
Width	280mm
Flow rate	9 lpm
Temperature limiter	38°C
Finish	Chrome-plated brass
Norms	   
Warranty	