

# SECURITHERM thermostatic shower mixer

Ref. H9739S

Dual control thermostatic shower mixer



## DESCRIPTION

**SECURITHERM thermostatic shower mixer - Ref. H9739S**

SECURITHERM dual control thermostatic shower mixer. Mixer with anti-scalding safety: shuts off automatically if the cold water supply fails.

Prevents cold showers: shuts off automatically if the hot water supply fails.

Scale-resistant thermostatic cartridge for temperature adjustment.

1/4-turn ceramic head for flow rate adjustment.

Temperature control from 25 - 40°C with maximum temperature limiter set at 38°C.

Thermal shocks are possible without removing the control knob and shutting off the cold water.

Flow rate regulated at 9 lpm.

Chrome-plated brass body and CLASSIC controls.

M1/2" shower outlet.

Filters and non-return valves integrated on the F3/4" inlets.

Mixer with offset standard wall connectors, M1/2" M3/4".

Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Suitable for people with reduced mobility.

30-year warranty.

## ADVANTAGES



SECURITHERM: Optimum anti-scalding safety



Pre-set maximum temperature limiter







Thermostatic: total temperature stability



Ergonomic: controls are easy to grip

## TECHNICAL CHARACTERISTICS

**SECURITHERM thermostatic shower mixer - Ref. H9739S**

Connector	M1/2"
Technology	SECURITHERM thermostatic mixer
Width	280mm
Flow rate	9 lpm
Temperature limiter	38°C
Finish	Chrome-plated brass
Norms	   
Warranty	