

SECURITHERM securitouch thermostatic shower kit

Ref. H9739KIT

Shower kit with thermostatic mixer

DESCRIPTION

SECURITHERM securitouch thermostatic shower kit - Ref. H9739KIT

SECURITHERM dual control thermostatic shower kit:

- Shower mixer with scale-resistant, thermostatic cartridge: Mixer with anti-scalding failsafe: shuts off automatically if cold water supply fails.

Prevents cold showers: shuts off automatically if hot water supply fails.

Scale-resistant thermostatic cartridge for temperature adjustment.

1/4-turn ceramic head for flow rate adjustment.

Temperature control from 25 - 40°C with temperature limiter set at 38°C.

Thermal shocks are possible without removing the control knob or shutting off the cold water supply.

Flow rate regulated at 9 lpm.

Chrome-plated brass body with CLASSIC controls.

M1/2" shower outlet.

Filters and non-return valves integrated in F3/4" inlets.

Mixer with offset STOP/CHECK wall connectors, M1/2" M3/4".

- Sliding shower head holder (ref. 813) on a chrome-plated riser rail (ref. 821) with soap dish and flexible shower hose (ref. 836T1).

- Shower hose retaining collar (ref. 830).



Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Mixer suitable for people with reduced mobility.

Shower mixer with 30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM securitouch thermostatic shower kit - Ref. H9739KIT

Connector	M1/2"
Technology	SECURITHERM thermostatic mixer
Width	280mm
Flow rate	9 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	ACS 
Warranty	



ADVANTAGES



SECURITHERM: Optimum anti-scalding safety




Pre-set maximum temperature limiter



Thermostatic: total temperature stability



Ergonomic: controls are easy to grip



Repairability

