

Aluminium shower panel with SECURITHERM sequential mixer

Ref. H9639

Sequential thermostatic mixer





DESCRIPTION

Aluminium shower panel with SECURITHERM sequential mixer - Ref. H9639

Anodised aluminium shower panel for wall-mounted exposed installation: SECURITHERM sequential thermostatic mixer (non-time flow).
 Adjustable temperature control from cold water up to 39°C; maximum temperature limiter set at 39°C, can be adjusted.
 Anti-scalding failsafe: automatic shut-off if cold water supply fails.
 Anti-cold showers function: automatic shut-off if hot water fails.
 Thermal shocks are possible.
 Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation at 6 lpm at 3 bar.
 Hygiene control lever L. 100mm.
 Top inlets with inline M1/2" stopcocks.
 Concealed fixings.
 Filters.
 Suitable for people with reduced mobility.
 30-year warranty.





TECHNICAL CHARACTERISTICS

Aluminium shower panel with SECURITHERM sequential mixer - Ref. H9639

| | |
|---------------------|---|
| Supply | Top inlets with M1/2" inline stopcocks |
| Connector | M1/2" |
| Technology | Sequential thermostatic SECURITHERM |
| Height | 1050mm |
| Width | 210mm |
| Flow rate | 6 lpm |
| Temperature limiter | 39°C |
| Finish | Aluminium |
| Norms | ACS   |
| Warranty |  |
| Repairability |  |



ADVANTAGES

-  SECURITHERM: Optimum anti-scalding safety
-  No non-return valves on inlets
-  Thermostatic: total temperature stability
-  Sequential open and closing on cold water

