

# Aluminium shower panel with SECURITHERM sequential mixer

Ref. H9639

Sequential thermostatic mixer





## DESCRIPTION

**Aluminium shower panel with SECURITHERM sequential mixer - Ref. H9639**

Anodised aluminium shower panel for wall-mounted exposed installation: SECURITHERM sequential thermostatic mixer (non-time flow).  
 Adjustable temperature control from cold water up to 39°C; maximum temperature limiter set at 39°C, can be adjusted.  
 Anti-scalding failsafe: automatic shut-off if cold water supply fails.  
 Anti-cold showers function: automatic shut-off if hot water fails.  
 Thermal shocks are possible.  
 Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation at 6 lpm at 3 bar.  
 Comfortable, rain-effect spray.  
 Hygiene control lever L. 100mm.  
 Top inlets with inline M1/2" stopcocks.  
 Concealed fixings.  
 Filters.  
 Suitable for people with reduced mobility.  
 30-year warranty.





## TECHNICAL CHARACTERISTICS

**Aluminium shower panel with SECURITHERM sequential mixer - Ref. H9639**

Supply	Top inlets with M1/2" inline stopcocks
Connector	M1/2"
Technology	Sequential thermostatic SECURITHERM
Height	1050mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	39°C
Finish	Aluminium
Norms	ACS  
Warranty	
Repairability	



## ADVANTAGES

-  SECURITHERM: Optimum anti-scalding safety
-  No non-return valves on inlets
-  Thermostatic: total temperature stability
-  Sequential open and closing on cold water

