BINOPTIC electronic tap

Ref. 378015

Mains supply



ADVANTAGES

BINOPTIC electronic tap - Ref. 378015Deck-mounted electronic basin tap:

Independent IP65 electronic control unit. 230/12V mains supply with transformer.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.

Scale-resistant flow straightener.

Adjustable duty flush (pre-set flush ~60 seconds every 24hr after last use).

Active, infrared presence detection, sensor at the end of the spout optimises detection.

Chrome-plated brass body.

PEX flexible with filter and solenoid valve M3/8".

Fixing reinforced by 2 stainless steel rods.

Anti-blocking security.


DESCRIPTION


Spout with smooth interior and low volume of water (reduces niches where bacteria can develop).

Suitable for people with reduced mobility.

30-year warranty.

90% water savings








TECHNICAL CHARACTERISTICS

BINOPTIC electronic tap - Ref. 378015

Supply	230/12V mains supply
Connector	M3/8"
Technology	Electronic
Drop height	90mm
Spout length	125mm
Flow rate	3 lpm
Norms	ACS (€ W () ()
Warranty	30 S
Repairability	50 g



© DELABIE https://www.delabie.co.uk