

SECURITHERM shower panel

Ref. 792380

Thermostatic mechanical dual control




DESCRIPTION

SECURITHERM shower panel - Ref. 792380

Dual control thermostatic shower panel:
 Anodised aluminium shower panel for wall-mounted, exposed installation.
 Concealed inlet via flexibles M $\frac{1}{2}$ ".
 SECURITHERM thermostatic mixer.
 Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.
 Anti-scalding failsafe: automatic shut-off if cold water fails.
 Anti-cold showers function: automatic shut-off if hot water fails.
 Thermal shocks are possible.
 Non-time flow 1/4-turn valves to control flow.
 Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation set at 6 lpm at 3 bar.
 Handset with removable flexible via push-fit rapid STOP connector and wall support supplied.
 Concealed fixings.
 Filters and non-return valves.
 Suitable for people with reduced mobility.
 30-year warranty.





TECHNICAL CHARACTERISTICS

SECURITHERM shower panel - Ref. 792380

| | |
|---------------------|---|
| Connector | M $\frac{1}{2}$ " |
| Technology | Non-time flow |
| Height | 1050mm |
| Depth | 67mm |
| Width | 210mm |
| Flow rate | 6 lpm |
| Temperature limiter | Thermostatic |
| Finish | Aluminium |
| Norms | ACS   |
| Warranty |  |



ADVANTAGES

-  Thermostatic control
-  Instant shut-off if cold water fails
-  Fixed shower head or handset
-  Aluminium panel, brass controls

