

TEMPOMIX time flow shower panel

Ref. 790310

Time flow single control

DESCRIPTION

TEMPOMIX time flow shower panel - Ref. 790310

Time flow shower panel with fixed shower head:
 Anodised aluminium shower panel for wall-mounted, exposed installation.
 Concealed inlet via flexibles M $\frac{1}{2}$ ".
 TEMPOMIX shower mixer with adjustable maximum temperature limiter.
 Soft-touch operation.
 Time flow ~30 seconds.
 Flow rate 6 lpm at 3 bar.
 Chrome-plated tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation.
 Concealed fixings.
 Filters and non-return valves.
 Shower panel suitable for people with reduced mobility.
 30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMIX time flow shower panel - Ref. 790310

| | |
|------------|---|
| Connector | M $\frac{1}{2}$ " |
| Technology | Time flow |
| Height | 1,050mm |
| Depth | 65mm |
| Width | 210mm |
| Flow rate | 6 lpm |
| Finish | Aluminium |
| Norms |     |
| Warranty |  |



ADVANTAGES



80% water savings



Temperature control on the mixer



Aluminium panel, brass controls

