

## TEMPOMIX time flow shower kit

Ref. 790909

Single control time flow



### DESCRIPTION

**TEMPOMIX time flow shower kit - Ref. 790909**

Time flow shower kit with recessed waterproof housing:  
 Chrome-plated wall plate Ø 195mm.  
 Standard recessed housing.  
 Recessing depth can be adjusted from 28 to 43mm.  
 TEMPOMIX ¼" single control mixer.  
 Ligature-resistant collar.  
 Temperature control and operation via the push-button.  
 Maximum temperature limiter (can be adjusted by the installer).  
 Time flow ~30 seconds.  
 Flow rate 6 lpm at 3 bar.  
 Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.  
 M½" connectors for copper tubes Ø 14mm.  
 Integrated non-return valves and filters.  
 Chrome-plated metal push-button.  
 Suitable for people with reduced mobility.  
 30-year warranty.  
 Integrated non-return valves and filters. This model does not have a waterproof recessing box. The installer must ensure that the recessing area is waterproof and any leaks or condensates can drain away (see installation guide).

### ADVANTAGES



80% water savings



Wall recessed installation





Time flow system tested to over 500,000 operations



Soft-touch operation

### TECHNICAL CHARACTERISTICS

**TEMPOMIX time flow shower kit - Ref. 790909**

Connector	½"
Technology	Time flow
Flow rate	6 lpm
Norms	ACS  
Warranty	