

TEMPOMIX time flow shower kit

Ref. 790709

Single control time flow



DESCRIPTION

TEMPOMIX time flow shower kit - Ref. 790709

Recessed time flow shower kit:
 Stainless steel wall plate 160 x 160mm.
 Standard recessing housing.
 Recessing depth can be adjusted from 28 to 48mm.
 TEMPOMIX ¾" single control mixer.
 Ligature-resistant collar.
 Temperature control and operation via the push-button.
 Maximum temperature limiter (can be adjusted by the installer).
 Time flow ~30 seconds, soft-touch operation.
 Flow rate 6 lpm at 3 bar.
 Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.
 M½" connections for copper tubes Ø 14mm.
 Integrated non-return valves and filters.
 Chrome-plated metal control.
 30-year warranty.
 This model does not have a waterproof recessing box. The installer must ensure that the recessing area is waterproof and any leaks or condensates can drain away (see installation guide).

ADVANTAGES



80% water savings



Wall recessed installation



Time flow system tested to over 500,000 operations



Soft-touch operation

TECHNICAL CHARACTERISTICS

TEMPOMIX time flow shower kit - Ref. 790709

Connector	½"
Technology	Time flow
Height	160mm
Width	160mm
Flow rate	6 lpm
Norms	ACS  
Warranty	

