

# TEMPOMIX time flow shower kit

Ref. 790709

Single control time flow







## DESCRIPTION

### TEMPOMIX time flow shower kit - Ref. 790709



Recessed time flow shower kit:  
 Stainless steel wall plate 160 x 160mm.  
 Standard recessing housing.  
 Recessing depth can be adjusted from 28 to 48mm.  
 TEMPOMIX 3/4" single control mixer.  
 Ligature-resistant collar.  
 Temperature control and operation via the push-button.  
 Maximum temperature limiter (can be adjusted by the installer).  
 Time flow ~30 seconds, soft-touch operation.  
 Flow rate 6 lpm at 3 bar.  
 Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.  
 M1/2" connections for copper tubes Ø 14mm.  
 Integrated non-return valves and filters.  
 Chrome-plated metal control.  
 30-year warranty.  
 This model does not have a waterproof recessing box. The installer must ensure that the recessing area is waterproof and any leaks or condensates can drain away (see installation guide).

## ADVANTAGES

-  80% water savings
-  Wall recessed installation
-  Time flow system tested to over 500,000 operations
-  Soft-touch operation

## TECHNICAL CHARACTERISTICS

### TEMPOMIX time flow shower kit - Ref. 790709

Connector	1/2"
Technology	Time flow
Height	160mm
Width	160mm
Flow rate	6 lpm
Norms	ACS  
Warranty	