

# TEMPOMIX time flow shower mixer

Ref. 790927

Single control time flow



## DESCRIPTION

**TEMPOMIX time flow shower mixer - Ref. 790927**

Recessed time flow shower mixer:  
 Chrome-plated metal wall plate Ø 195mm.  
 Standard recessing housing.  
 Recessing depth can be adjusted from 28 - 43mm.  
 TEMPOMIX ¾" single control mixer.  
 Ligature-resistant collar.  
 Temperature control and operation via the push-button.  
 Maximum temperature limiter (can be adjusted by the installer).  
 Time flow ~30 seconds.  
 Flow rate 12 lpm at 3 bar.  
 M½" connectors for Ø 14mm copper tubes.  
 Chrome-plated metal control.  
 Integrated non-return valves and filters.  
 30-year warranty.  
 This model does not have a waterproof recessing box. The installer must ensure that the recessing area is waterproof and any leaks or condensates can drain away (see installation guide).

## ADVANTAGES



Wall recessed installation



Time flow system tested to over 500,000 operations



Soft-touch operation

## TECHNICAL CHARACTERISTICS

**TEMPOMIX time flow shower mixer - Ref. 790927**

Connector	½"
Technology	Time flow
Flow rate	12 lpm
Norms	
Warranty	

