

TEMPOMIX time flow shower mixer

Ref. 790427

Single control time flow



DESCRIPTION

TEMPOMIX time flow shower mixer - Ref. 790427

Recessed time flow shower kit:
 Stainless steel wall plate 160 x 160mm.
 Standard recessing housing.
 Recessing depth can be adjusted from 28 to 48mm.
 TEMPOMIX 3/4" single control mixer.
 Ligature-resistant collar.
 Temperature control and operation via the push-button.
 Maximum temperature limiter (can be adjusted by the installer).
 Time flow ~30 seconds.
 Flow rate 12 lpm at 3 bar.
 M1/2" connections for Ø 14mm copper tubes.
 Integrated non-return valves and filters.
 Chrome-plated metal push-button.
 Integrated non-return valves and filters.
 30-year warranty.
 This model does not have a waterproof recessing box. The installer must ensure that the recessing area is waterproof and any leaks or condensates can drain away (see installation guide).

TECHNICAL CHARACTERISTICS

TEMPOMIX time flow shower mixer - Ref. 790427

Connector	1/2"
Technology	Time flow
Height	160mm
Width	160mm
Flow rate	12 lpm
Norms	
Warranty	

ADVANTAGES



Wall recessed installation



System tested to over 500000 operations



Soft-touch operation

