

TEMPOMATIC urinal valve

Ref. 428150

Electronic mains supply





DESCRIPTION

TEMPOMATIC urinal valve - Ref. 428150

Cross wall electronic urinal valve:
 Mains supply, electronic control unit 12V with solenoid valve, filter and stopcock M $\frac{1}{2}$ ".
 Cross wall installation for walls \leq 155mm.
 Shock-resistant infrared presence detector.
 Detection distance, time flow and flow rate can be adjusted during installation.
 Order the 230/12V transformer separately.
 Presence detection delay is 3 sec.
 Automatic pre-rinse possible.
 Time flow 3 seconds, can be adjusted from 3 - 12 sec.
 Hygienic duty flush every 24 hours after last use, prevents vacuums.
 Flow rate 0.3 L/sec. at 3 bar pressure, can be adjusted.
 Wall plate flush to the wall.
 Threaded rods can be cut-to-size.
 Compatible with rain water.
 Suitable for people with reduced mobility.
 30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC urinal valve - Ref. 428150

Supply	12V mains supply
Connector	$\frac{1}{2}$ "
Technology	Electronic
Length	155mm
Flow rate	0.3 l/sec.
Norms	
Warranty	

ADVANTAGES



Total hygiene: no manual contact



ECO time flow set at 3 seconds



Cross wall installation



Hygienic duty flush

