

# TEMPOMATIC urinal valve

Ref. 428200

Electronic mains supply





## DESCRIPTION

### TEMPOMATIC urinal valve - Ref. 428200





Cross wall electronic urinal valve:  
 Mains supply, electronic control unit 12V with solenoid valve, filter and stopcock M $\frac{1}{2}$ ".  
 Cross wall installation for walls  $\leq$  225mm.  
 Shock-resistant infrared presence detector.  
 Detection distance, time flow and flow rate can be adjusted at installation.  
 Order the 230/12V transformer separately.  
 Presence detection delay is 3 seconds.  
 Automatic pre-rinse possible.  
 Time flow 3 sec. can be adjusted from 3 - 12 seconds.  
 Hygienic duty flush is possible every 24 hours after last use, prevents vacuums.  
 Flow rate 0.3 L/sec. at 3 bar pressure, can be adjusted.  
 Wall plate flush to the wall.  
 Threaded rods can be cut-to-size.  
 Compatible with rain water.  
 Suitable for people with reduced mobility.  
 30-year warranty.

## TECHNICAL CHARACTERISTICS

### TEMPOMATIC urinal valve - Ref. 428200

Supply	Secteur 12V
Connector	1/2"
Technology	Electronic
Length	225mm
Flow rate	0.3 l/sec.
Norms	
Warranty	

## ADVANTAGES

-  Total hygiene: no manual contact
-  ECO time flow 3 seconds
-  Cross wall installation
-  Hygienic duty flush

