

## TEMPOFLUX 2 direct flush valve

Ref. 762902

Time flow direct flush WC valve



### DESCRIPTION

TEMPOFLUX 2 direct flush valve - Ref. 762902

Flush system without cistern: directly connected to pipework.  
 Chrome-plated metal wall plate Ø 195mm.  
 Concealed mechanical fixing of the wall plate.  
 Multipurpose recessing housing.  
 Recessing depth can be adjusted from 0 - 20mm.  
 3L/6L dual flush, can be adjusted to 2L/4L.  
 Soft-touch operation.  
 Vacuum breaker.  
 Integrated stopcock and flow rate / flush volume adjuster.  
 Solid brass body.  
 Chrome-plated metal push-button.  
 In-line inlet M $\frac{3}{4}$ ".  
 Outlet connection for PVC tube Ø 26/32mm.  
 Acoustic level complies with European standard EN 12541 class II.  
 Upstream supply pipes: minimum Ø 20mm required at all points (including connectors).  
 Base flow rate: 1L/sec at 1 bar dynamic pressure.  
 Compatible with rain water.  
 Suitable for rimless WC pans without flow rate regulation and suitable for people with reduced mobility.  
 30-year warranty.  
 This model does not have a waterproof recessing housing. The installer must ensure that the recessing area is waterproof and any leaks or condensation can drain away (see installation guide).

### ADVANTAGES



Soft-touch operation



Dual flush 3L/6L





No cistern: no stagnant water



Recessed installation

### TECHNICAL CHARACTERISTICS

TEMPOFLUX 2 direct flush valve - Ref. 762902

Connector	3/4"
Technology	Time flow
Flow rate	3L/6L
Finish	Chrome-plated metal
Norms	 
Warranty	