

## TEMPOFLUX 1 direct flush valve

Ref. 761627

Time flow direct flush WC valve






### DESCRIPTION

TEMPOFLUX 1 direct flush valve - Ref. 761627

Recessed time flow valve for direct flush:  
 Stainless steel control plate 220 x 170mm.  
 Multipurpose recessing housing.  
 Soft-touch operation.  
 Time flow ~7 seconds.  
 Vacuum breaker.  
 Integrated stopcock and flow/volume rate adjuster.  
 Solid brass body and chrome-plated push-button.  
 In-line inlet M $\frac{3}{4}$ ".  
 Outlet connection for PVC tube  $\varnothing$  26/32mm.  
 Upstream supply pipes: minimum  $\varnothing$  20mm required at all points (including connectors).  
 Base flow rate: 1 L/sec at 1 bar dynamic pressure.  
 Compatible with rain water.  
 Suitable for people with reduced mobility.  
 30-year warranty.  
 This model does not have a waterproof recessing housing. The installer must ensure that the recessing area is waterproof and any leaks or condensation can drain away (see installation guide).

### TECHNICAL CHARACTERISTICS

TEMPOFLUX 1 direct flush valve - Ref. 761627

Connector	3/4"
Height	220mm
Width	170mm
Norms	 
Warranty	

### ADVANTAGES



No cistern: no stagnant water



Wall recessed installation



Powerful flush and immediately available



Direct flush reduces the risk of leaks

