

## TEMPOFLUX 1 direct flush valve

Ref. 761900

Direct flush WC valve



### DESCRIPTION

TEMPOFLUX 1 direct flush valve - Ref. 761900

Flush system without cistern: directly connected to pipework.  
 Chrome-plated brass wall plate Ø 195mm.  
 Multipurpose recessing housing.  
 Soft-touch operation.  
 Time flow ~7 seconds.  
 Vacuum breaker.  
 Integrated stopcock and flow/volume rate adjuster.  
 Solid brass body and chrome-plated push-button.  
 In-line inlet M $\frac{3}{4}$ ".  
 Outlet connection for PVC tube Ø 25mm.  
 Upstream supply pipes: minimum Ø 20mm required at all points (including connectors).  
 Base flow rate: 1L/sec at 1 bar dynamic pressure.  
 30-year warranty.  
 This model does not have a waterproof recessing housing. The installer must ensure that the recessing area is waterproof and any leaks or condensation can drain away (see installation guide).

### ADVANTAGES



No cistern: no stagnant water



Wall recessed installation






Powerful flush and immediately available



Direct flush reduces the risk of leaks

### TECHNICAL CHARACTERISTICS

TEMPOFLUX 1 direct flush valve - Ref. 761900

Connector	$\frac{3}{4}$ "
Norms	 
Warranty	
Repairability	