

TEMPOFLUX 1 direct flush valve

Ref. 761900

Direct flush WC valve



DESCRIPTION

TEMPOFLUX 1 direct flush valve - Ref. 761900

Flush system without cistern: directly connected to pipework.
 Chrome-plated brass wall plate Ø 195mm.
 Multipurpose recessing housing.
 Soft-touch operation.
 Time flow ~7 seconds.
 Vacuum breaker.
 Integrated stopcock and flow/volume rate adjuster.
 Solid brass body and chrome-plated push-button.
 In-line inlet M $\frac{3}{4}$ ".
 Outlet connection for PVC tube Ø 25mm.
 Upstream supply pipes: minimum Ø 20mm required at all points (including connectors).
 Base flow rate: 1L/sec at 1 bar dynamic pressure.
 30-year warranty.
 This model does not have a waterproof recessing housing. The installer must ensure that the recessing area is waterproof and any leaks or condensation can drain away (see installation guide).

ADVANTAGES



No cistern: no stagnant water



Wall recessed installation







Powerful flush and immediately available



Direct flush reduces the risk of leaks

TECHNICAL CHARACTERISTICS

TEMPOFLUX 1 direct flush valve - Ref. 761900

| | |
|---------------|---|
| Connector | $\frac{3}{4}$ " |
| Norms |   |
| Warranty |  |
| Repairability |  |

