

## TEMPOFLUX 1 direct flush kit

Ref. 761003

Time flow direct flush WC valve






### DESCRIPTION

TEMPOFLUX 1 direct flush kit - Ref. 761003

Flush system without cistern: directly connected to pipework.  
 For wall-mounted exposed installation.  
 Soft-touch operation.  
 Time flow ~7 seconds.  
 Vacuum breaker.  
 Integrated stopcock and flow rate / flush volume rate adjuster.  
 Chrome-plated solid brass body and push-button.  
 Angled inlet M $\frac{3}{4}$ ".  
 Upstream supply pipes: minimum  $\varnothing$  20mm required at all points (including connectors).  
 Base flow rate: 1 L/sec at 1 bar dynamic pressure.  
 With stainless steel flush tube, collar and connection washer.  
 Compatible with rain water.  
 Suitable for people with reduced mobility.  
 30-year warranty.

### TECHNICAL CHARACTERISTICS

TEMPOFLUX 1 direct flush kit - Ref. 761003

Connector	$\frac{3}{4}$ "
Height	565mm
Length	215mm
Norms	 
Warranty	

### ADVANTAGES



No cistern: no stagnant water



Chrome-plated solid brass



Powerful flush and immediately available



Direct flush reduces the risk of leaks

