

TEMPOMATIC MIX 4 electronic mixer

Ref. 49000615

Integrated batteries, stopcocks Ø 15mm






DESCRIPTION

TEMPOMATIC MIX 4 electronic mixer - Ref. 49000615





Deck-mounted electronic basin mixer:
 Battery-operated with integrated 123 6V Lithium batteries.
 Reduced stagnation solenoid valve and electronic unit integrated into the body of the mixer.
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
 Scale-resistant flow straightener.
 Duty flush (~60 seconds every 24 hours after last use).
 Presence detection sensor at the end of the spout optimises detection.
 Chrome-plated stainless steel body.
 Cap fixed in place by two concealed screws.
 PEX flexibles Ø 15mm for compression fittings with stopcocks, filters and non-return valves.
 Fixing reinforced by 2 stainless steel rods.
 Anti-blocking security.
 Side temperature control with adjustable maximum temperature limiter.
 Suitable for people with reduced mobility.
 30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC MIX 4 electronic mixer - Ref. 49000615

Supply	6V batteries
Connector	M½" Ø 15mm
Technology	Electronic
Drop height	70mm
Spout length	105mm
Flow rate	3 lpm
Norms	
Warranty	
Repairability	

ADVANTAGES

-  Exceptional water savings: 90%
-  Hygiene: no manual contact
-  Batteries integrated in mixer body
-  Integrated solenoid valve

