

TEMPOMATIC MIX 4 electronic mixer

Ref. 49000615

Integrated batteries, stopcocks Ø 15mm






DESCRIPTION

TEMPOMATIC MIX 4 electronic mixer - Ref. 49000615

Deck-mounted electronic basin mixer:
 Battery-operated with integrated 123 6V Lithium batteries.
 Reduced stagnation solenoid valve and electronic unit integrated into the body of the mixer.
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
 Scale-resistant flow straightener.
 Duty flush (~60 seconds every 24 hours after last use).
 Presence detection sensor at the end of the spout optimises detection.
 Chrome-plated stainless steel body.
 Cap fixed in place by two concealed screws.
 PEX flexibles Ø 15mm for compression fittings with stopcocks, filters and non-return valves.
 Fixing reinforced by 2 stainless steel rods.
 Anti-blocking security.
 Side temperature control with adjustable maximum temperature limiter.
 Suitable for people with reduced mobility.
 30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC MIX 4 electronic mixer - Ref. 49000615

| | |
|---------------|---|
| Supply | 6V batteries |
| Connector | M½" Ø 15mm |
| Technology | Electronic |
| Drop height | 70mm |
| Spout length | 105mm |
| Flow rate | 3 lpm |
| Norms |  |
| Warranty |  |
| Repairability |  |

ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Batteries integrated in mixer body



Integrated solenoid valve

