

TEMPOMATIC electronic shower kit

Ref. 452159

Electronic




DESCRIPTION

TEMPOMATIC electronic shower kit - Ref. 452159

Cross wall electronic shower kit:
 TEMPOMATIC electronic valve for mixed water supply.
 For walls ≤ 155mm.
 Power supply by electronic unit with solenoid valve 1/2".
 230/12V transformer.
 2 operation modes:
 - Automatic activation via presence detection.
 - Voluntary ON/OFF activation by passing the hand in front of sensor ~10 cm.
 Duty flush (~60 seconds every 24 hours after the last use).
 Adjustable time flow from 30 to 60 seconds.
 Flow rate set at 6 lpm at 3 bar.
 Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.
 Chrome-plated solid brass.
 Wall plate flush to the wall.
 Threaded rods can be cut-to-size.
 Electronic shower kit suitable for people with reduced mobility.
 30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC electronic shower kit - Ref. 452159

Supply	230/12V mains supply
Connector	1/2"
Technology	Electronic
Length	155mm
Flow rate	6 lpm
Norms	ACS CE
Warranty	

ADVANTAGES



230/12V



Total hygiene: no manual contact



Anti-bacterial duty flush



2 operation modes

