

# SECURITHERM time flow shower panel

Ref. 792314

Time flow thermostatic






## DESCRIPTION

**SECURITHERM time flow shower panel - Ref. 792314**





Thermostatic time flow shower panel:  
 Large model satin stainless steel shower panel for wall-mounted, exposed installation.  
 Concealed inlet via flexibles M $\frac{1}{2}$ ".  
 SECURITHERM thermostatic shower mixer.  
 Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.  
 Anti-scalding failsafe: automatic shut-off if cold water fails.  
 Anti-cold showers function: automatic shut-off if hot water fails.  
 Thermal shocks are possible.  
 Soft-touch operation.  
 Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation.  
 Time flow ~30 seconds.  
 Flow rate 6 lpm at 3 bar.  
 Integrated soap dish.  
 M $\frac{1}{2}$ " stopcocks.  
 Concealed fixings.  
 Filters and non-return valves.  
 Shower panel suitable for people with reduced mobility.  
 30-year warranty.

## TECHNICAL CHARACTERISTICS

**SECURITHERM time flow shower panel - Ref. 792314**

|                     |   |
|---------------------|---|
| Connector           | M1/2"   |
| Technology          | Time flow   |
| Height              | 1220mm  |
| Depth               | 100mm   |
| Width               | 250mm   |
| Flow rate           | 6 lpm   |
| Temperature limiter | Thermostatic  |
| Finish              | Stainless steel   |
| Norms               | ACS   |
| Warranty            |    |

## ADVANTAGES

-  Thermostatic control
-  Instant shut-off if cold water fails
-  80% water savings
-  Stainless steel panel, brass controls

