

SECURITHERM time flow shower panel

Ref. 792313

Time flow thermostatic



DESCRIPTION

SECURITHERM time flow shower panel - Ref. 792313





Thermostatic time flow shower panel:
 Large model satin stainless steel shower panel for wall-mounted, exposed installation.
 Concealed inlet via flexibles M $\frac{1}{2}$ ".
 SECURITHERM thermostatic shower mixer.
 Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.
 Anti-scalding failsafe: automatic shut-off if cold water fails.
 Anti-cold showers function: automatic shut-off if hot water fails.
 Thermal shocks are possible.
 Soft-touch operation.
 Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation.
 Time flow ~30 seconds.
 Flow rate 6 lpm at 3 bar.
 M $\frac{1}{2}$ " stopcocks.
 Concealed fixings.
 Filters and non-return valves.
 Shower panel suitable for people with reduced mobility.
 30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM time flow shower panel - Ref. 792313

| | |
|---------------------|---|
| Connector | M $\frac{1}{2}$ " |
| Technology | Time flow |
| Height | 1,220mm |
| Depth | 100mm |
| Width | 250mm |
| Flow rate | 6 lpm |
| Temperature limiter | Thermostatic |
| Finish | Stainless steel |
| Norms | ACS STF |
| Warranty |  |

ADVANTAGES

-  Thermostatic control
-  Instant shut-off if cold water fails
-  80% water savings
-  Aluminium panel, brass controls

