

## TEMPOFLUX time flow urinal valve

Ref. 778755

Time flow 3 seconds. For standard urinals Ø 35mm. Straight neck tube






### DESCRIPTION

TEMPOFLUX time flow urinal valve - Ref. 778755

Exposed time flow urinal valve:  
 For standard or siphon action urinals.  
 For wall-mounted exposed installation.  
 Soft-touch operation.  
 Time flow pre-set at 3 seconds.  
 Vacuum breaker.  
 Flow rate pre-set at 0.15 l/sec. at 3 bar, can be adjusted up to 0.3 l/sec.  
 Innovative stopcock and flow rate adjustment system integrated in the wall plate (patented).  
 Compatible with rain water.  
 Complies with European standard EN 12541 (acoustic level class II).  
 Chrome-plated solid brass body M $\frac{1}{2}$ ".  
 With a chrome-plated neck tube and connection washer Ø 35mm.  
 Angled for recessed inlet.  
 Suitable for people with reduced mobility.  
 30-year warranty.

### TECHNICAL CHARACTERISTICS

TEMPOFLUX time flow urinal valve - Ref. 778755

Connector	$\frac{1}{2}$ "
Technology	Time flow
Height	320mm
Flow rate	0.15 l/sec.
Norms	 
Warranty	

### ADVANTAGES



Eco time flow 3 seconds



Soft-touch operation



Stopcock built-in to wall plate



Smooth design

