

SECURITHERM shower panel

Ref. 792504

Electronic mains supply thermostatic




DESCRIPTION

SECURITHERM shower panel - Ref. 792504





Electronic thermostatic shower panel:
 Large stainless steel panel for wall-mounted, exposed installation.
 Top inlet via in-line stopcocks M $\frac{1}{2}$ ".
 SECURITHERM thermostatic mixer.
 Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.
 Anti-scalding failsafe: automatic shut-off if cold water fails.
 Anti-cold showers function: automatic shut-off if hot water fails.
 Thermal shocks are possible.
 Mains supply 230/6V.
 Shower starts when electronic push-button is pressed.
 Shuts off voluntarily or automatically after ~60 seconds.
 Duty flush (~60 seconds every 24 hours after the last use).
 Flow rate 6 lpm at 3 bar, can be adjusted, rain-effect spray.
 Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.
 Integrated soap dish.
 Concealed fixings.
 Filters and non-return valves.
 Suitable for people with reduced mobility.
 30-year warranty.


TECHNICAL CHARACTERISTICS

SECURITHERM shower panel - Ref. 792504

Supply	230/6V mains supply
Connector	M $\frac{1}{2}$ "
Technology	Electronic
Height	1220mm
Depth	100mm
Width	250mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Stainless steel
Norms	ACS  

ADVANTAGES

-  Exceptional water savings: 80%
-  Anti-bacterial proliferation duty flush
-  Thermostatic temperature regulation
-  Instant shut-off if cold water fails



Warranty

