TEMPOMIX 3 time flow shower kit

Ref. 794450

Time flow single control

DESCRIPTION TEMPOMIX 3 time flow shower kit - Ref. 794450

Exposed time flow shower kit: TEMPOMIX 3 single control mixer ³/₄", top outlet. For wall-mounted, exposed installation. Temperature control and operation via the push-button. Maximum temperature limiter (can be adjusted by the installer). Soft-touch operation. Time flow \sim 30 seconds. Flow rate 6 lpm at 3 bar. Chrome-plated, tamperproof, scale-resistant TONIC JET shower head with automatic flow rate regulation. Chrome-plated solid brass. Integrated filters and non-return valves. Chrome-plated metal push-button. Shower column Ø 16mm with reinforced collar (fixing plate and screws included). $M^{1/2}$ " offset connectors for 130 - 170mm centres. Suitable for people with reduced mobility. 30-year warranty.

TECHNICAL CHARACTERISTICS


TEMPOMIX 3	time flow	shower kit	- Ref.	794450
------------	-----------	------------	--------	--------

Connector	M ¹ ⁄ ₂ "
Technology	Time flow
Height	1,010mm
Width	150mm
Flow rate	6 lpm
Norms	ACS 👪
Warranty	30 MARANTY





80% water savings





Time flow system tested to over 500,000 operations

