

TEMPOMIX 3 time flow shower kit

Ref. 794450

Time flow single control




DESCRIPTION

TEMPOMIX 3 time flow shower kit - Ref. 794450

Exposed time flow shower kit:
 TEMPOMIX 3 single control mixer ¾", top outlet.
 For wall-mounted, exposed installation.
 Temperature control and operation via the push-button.
 Maximum temperature limiter (can be adjusted by the installer).
 Soft-touch operation.
 Time flow ~30 seconds.
 Flow rate 6 lpm at 3 bar.
 Chrome-plated, tamperproof, scale-resistant TONIC JET shower head with automatic flow rate regulation.
 Chrome-plated solid brass.
 Integrated filters and non-return valves.
 Chrome-plated metal push-button.
 Shower column Ø 16mm with reinforced collar (fixing plate and screws included).
 M½" offset connectors for 130 - 170mm centres.
 Suitable for people with reduced mobility.
 30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMIX 3 time flow shower kit - Ref. 794450

Connector	M½"
Technology	Time flow
Height	1,010mm
Width	150mm
Flow rate	6 lpm
Norms	 ACS 
Warranty	



ADVANTAGES



80% water savings



Soft-touch operation



Time flow system tested to over 500,000 operations

