

TEMPOMIX 3 time flow shower mixer

Ref. 794470

Time flow single control



DESCRIPTION

TEMPOMIX 3 time flow shower mixer - Ref. 794470

Exposed time flow shower mixer:
 TEMPOMIX 3 single control mixer, bottom outlet, M $\frac{1}{2}$ " inlet with M $\frac{3}{4}$ " connector.
 Temperature control and operation via the push-button.
 Maximum temperature limiter (can be adjusted by the installer).
 For wall-mounted, exposed installation.
 Soft-touch operation.
 Time flow pre-set at ~30 seconds.
 Flow rate 6 lpm at 3 bar, can be adjusted from 6 lpm - 12 lpm.
 Chrome-plated solid brass.
 Integrated filters and non-return valves.
 Chrome-plated metal push-button.
 M $\frac{1}{2}$ " offset connectors for 130 - 170mm centres.
 Suitable for people with reduced mobility.
 30-year warranty.

ADVANTAGES







Soft-touch operation



Time flow system tested to over 500,000 operations

TECHNICAL CHARACTERISTICS

TEMPOMIX 3 time flow shower mixer - Ref. 794470

Connector	M $\frac{1}{2}$ "
Technology	Time flow
Width	150mm
Flow rate	9 lpm
Norms	   
Warranty	