

SECURITHERM Securitouch thermostatic shower mixer

Ref. H9741TP

Dual control thermostatic shower mixer




DESCRIPTION

SECURITHERM Securitouch thermostatic shower mixer - Ref. H9741TP





Dual control SECURITHERM thermostatic shower mixer.
 Mixer with anti-scalding safety: shuts off automatically if cold water fails.
 Prevents cold showers if hot water supply fails.
 Securitouch thermal insulation to prevent burns.
 Scale-resistant thermostatic cartridge for temperature adjustment.
 ¼-turn ceramic head for flow rate adjustment.
 Temperature adjusts from 25°C to 41°C.
 Maximum temperature limiter pre-set to 38°C.
 Thermal shocks are easy to undertake without shutting off the cold water.
 Flow rate regulated at 9 lpm.
 Chrome-plated brass body and ERGO controls.
 M1/2" shower outlet.
 Filters and non-return valves built-in to inlets F3/4".
 Mixer with inline STOP/CHECK connectors M1/2" M3/4".
 Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
 Mixer suitable for people with reduced mobility.
 Mixer with 30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM Securitouch thermostatic shower mixer - Ref. H9741TP

Connector	M1/2"
Technology	SECURITHERM Securitouch thermostatic mixer
Depth	92mm
Length	286mm
Flow rate	9 lpm
Temperature limiter	38°C
Finish	Chrome-plated brass
Warranty	

ADVANTAGES

-  SECURITHERM: Anti-scalding safety
-  Securitouch thermal insulation prevents burns
-  Thermostatic: complete temperature stability
-  Pre-set maximum temperature limiter

