

# SECURITHERM Securitouch thermostatic shower mixer

Ref. H9741TP

Dual control thermostatic shower mixer




## DESCRIPTION

**SECURITHERM Securitouch thermostatic shower mixer - Ref. H9741TP**





Dual control SECURITHERM thermostatic shower mixer.  
 Mixer with anti-scalding safety: shuts off automatically if cold water fails.  
 Prevents cold showers if hot water supply fails.  
 Securitouch thermal insulation to prevent burns.  
 Scale-resistant thermostatic cartridge for temperature adjustment.  
 ¼-turn ceramic head for flow rate adjustment.  
 Temperature adjusts from 25°C to 41°C.  
 Maximum temperature limiter pre-set to 38°C.  
 Thermal shocks are easy to undertake without shutting off the cold water.  
 Flow rate regulated at 9 lpm.  
 Chrome-plated brass body and ERGO controls.  
 M1/2" shower outlet.  
 Filters and non-return valves built-in to inlets F3/4".  
 Mixer with inline STOP/CHECK connectors M1/2" M3/4".  
 Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.  
 Mixer suitable for people with reduced mobility.  
 Mixer with 30-year warranty.

## TECHNICAL CHARACTERISTICS

**SECURITHERM Securitouch thermostatic shower mixer - Ref. H9741TP**

|                     |   |
|---------------------|---|
| Connector           | M1/2"   |
| Technology          | SECURITHERM Securitouch thermostatic mixer  |
| Depth               | 92mm  |
| Length              | 286mm   |
| Flow rate           | 9 lpm   |
| Temperature limiter | 38°C  |
| Finish              | Chrome-plated brass   |
| Warranty            |  |

## ADVANTAGES

-  SECURITHERM: Anti-scalding safety
-  Securitouch thermal insulation prevents burns
-  Thermostatic: complete temperature stability
-  Pre-set maximum temperature limiter

