TEMPOMIX 3 time flow mixer

Ref. 79400015

Soft-touch operation, Ø 15mm stopcocks



ADVANTAGES



Exceptional water savings: 85%



Soft-touch operation



Chrome-plated solid brass, reinforced fixings



Sleek design



Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.

Tamperproof scale-resistant flow straightener.

TEMPOMIX 3 time flow mixer - Ref. 79400015

Deck-mounted single control time flow basin mixer:

Temperature control and operation on the push-button.

Chrome-plated solid brass body.

Time flow pre-set at ~7 seconds.

DESCRIPTION

Soft-touch operation.

PEX flexibles with stopcocks, filters, non-return valves and Ø 15mm conical

Fixing reinforced by 2 stainless steel rods.

Adjustable maximum temperature limiter.


Suitable for people with reduced mobility.

30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMIX 3 time flow mixer - Ref. 79400015

Connector	M1/2" Ø 15mm
Technology	Time flow
Drop height	70mm
Spout length	105mm
Flow rate	3 lpm
Norms	UWRAS
Warranty	30 g



© DELABIE https://www.delabie.co.uk