

TEMPOMIX 3 time flow mixer

Ref. 79400015

Soft-touch operation, Ø 15mm stopcocks







DESCRIPTION

TEMPOMIX 3 time flow mixer - Ref. 79400015

Deck-mounted single control time flow basin mixer:
 Soft-touch operation.
 Temperature control and operation on the push-button.
 Time flow pre-set at ~7 seconds.
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.
 Tamperproof scale-resistant flow straightener.
 Chrome-plated solid brass body.
 PEX flexibles with stopcocks, filters, non-return valves and Ø 15mm conical inlets.
 Fixing reinforced by 2 stainless steel rods.
 Adjustable maximum temperature limiter.
 Suitable for people with reduced mobility.
 30-year warranty.
 *Add CR to the end of the reference (79400015CR) to order with copper tails.

ADVANTAGES

-  Exceptional water savings: 85%
-  Soft-touch operation
-  Chrome-plated solid brass, reinforced fixings
-  Sleek design

TECHNICAL CHARACTERISTICS

TEMPOMIX 3 time flow mixer - Ref. 79400015

Connector	M1/2" Ø 15mm
Technology	Time flow
Drop height	70mm
Spout length	105mm
Flow rate	3 lpm
Norms	
Warranty	