TEMPOMATIC 4 electronic tap

Ref. 44000015

Recessed mains supply, 15mm stopcock



DESCRIPTION

TEMPOMATIC 4 electronic tap - Ref. 44000015

Deck-mounted electronic basin tap:

230/6V recessed mains supply.

Reduced stagnation solenoid valve and electronic unit integrated into the body of the tap.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm. Scale-resistant flow straightener.

Duty flush (~60 sec. every 24h after last use).

Presence detection sensor at the end of the spout optimises detection.

Chrome-plated stainless steel body.

Cap fixed in place by two concealed screws.

PEX flexible with stopcock, filter and Ø 15mm conical inlet.

Fixing reinforced by 2 stainless steel rods.

Anti-blocking security.

Suitable for people with reduced mobility.

30-year warranty.

ADVANTAGES



Proven water savings: 90%



Hygiene: no manual contact



Recessed mains supply




Integrated solenoid valve

TECHNICAL CHARACTERISTICS

TEMPOMATIC 4 electronic tap - Ref. 44000015

Supply	230/6V (recessed mains supply)
Connector	M½" Ø 15mm
Technology	Electronic
Drop height	70mm
Spout length	105mm
Flow rate	3 lpm
Norms	C€
Warranty	30 S WASFANTY



© DELABIE https://www.delabie.co.uk