

## TEMPOSOFT MIX 2 time flow mixer

Ref. 74250015

Soft-touch operation, Ø 15mm stopcocks






### DESCRIPTION

TEMPOSOFT MIX 2 time flow mixer - Ref. 74250015




Deck-mounted time flow basin mixer:  
 Soft-touch operation.  
 Time flow ~7 seconds.  
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.  
 Tamperproof scale-resistant flow straightener.  
 Chrome-plated solid brass body.  
 PEX flexibles with stopcocks, filters, non-return valves and Ø 15mm conical inlets.  
 Fixing reinforced by 2 stainless steel rods.  
 Side temperature control with standard lever and maximum temperature limiter.  
 Suitable for people with reduced mobility.  
 30-year warranty.

### TECHNICAL CHARACTERISTICS

TEMPOSOFT MIX 2 time flow mixer - Ref. 74250015

Connector	M1/2" Ø 15mm
Technology	Time flow
Drop height	85mm
Spout length	100mm
Flow rate	3 lpm
Norms	
Warranty	
Repairability	

### ADVANTAGES

-  Exceptional water savings: 85%
-  Chrome-plated solid brass body
-  Soft-touch operation
-  Sleek design

