SECURITHERM shower panel

Ref. 79240015

Electronic battery-operated thermostatic

DESCRIPTION

SECURITHERM shower panel - Ref. 79240015

Thermostatic electronic shower panel:
Anodised aluminium shower panel for wall-mounted, exposed installation.
With top inlet via in-line stopcocks and Ø 15mm conical inlets.
SECURITHERM thermostatic shower mixer.
Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.
Anti-scalding failsafe: automatic shut-off if cold water fails.
Anti-cold showers function: automatic shut-off if hot water fails.
Thermal shocks are possible.
Battery-operated with CR-P2 223 6V Lithium battery.
Infrared presence detection. Shower starts when hand is 4cm from the sensor.
Shuts off on demand or automatically after ~60 seconds.
Duty flush (~60 seconds every 24 hours after the last use).
Flow rate set at 6 lpm at 3 bar.
Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation.
Concealed fixings.
Filters and non-return valves.
Electronic shower panel suitable for people with reduced mobility.
30-year warranty.

ADVANTAGES

- Total hygiene: operate without manual contact
- Duty flush limits bacterial proliferation
- Thermostatic temperature regulation
- Instant shut-off if cold water supply fails

TECHNICAL CHARACTERISTICS

SECURITHERM shower panel - Ref. 79240015

Supply	6V battery
Connector	M1/2'' Ø 15mm
Technology	Electronic
Height	1050mm
Depth	65mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Aluminium
Warranty	30 YEAR WARRANTY