

# Sequential thermostatic shower mixer

Ref. H964015

SECURITHERM sequential mixer, top outlet







## DESCRIPTION

**Sequential thermostatic shower mixer - Ref. H964015**



SECURITHERM thermostatic sequential shower mixer.  
 Thermostatic sequential mixer: opens and closes with cold water.  
 Mixer with no non-return valves (limits bacterial proliferation).  
 No risk of cross flow between hot and cold water.  
 Sequential mixer with anti-scalding safety: shuts off automatically if cold water supply fails.  
 Prevents cold showers: shuts off automatically if hot water supply fails.  
 Securitouch thermal insulation prevents burns.  
 Scale-resistant thermostatic sequential cartridge controls flow rate and temperature.  
 Temperature can be adjusted from cold water to 39°C with maximum temperature limiter set at 39°C.  
 Thermal shocks are possible.  
 Body with smooth interior and low water volume (reduces niches where bacteria can develop).  
 Flow rate regulated at 9 lpm.  
 Chrome-plated brass body and Hygiene control lever L. 100mm.  
 M3/4" top shower outlet.  
 Wall-mounted mixer with inline STOP/CHECK connectors, M1/2" M3/4".  
 Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.  
 Sequential mixer suitable for people with reduced mobility.  
 Shower mixer with 30-year warranty.

## ADVANTAGES

-  SECURITHERM: Anti-scalding safety
-  Securitouch thermal insulation prevents burns
-  No non-return valves on the inlets
-  Sequential open and closing on cold water

## TECHNICAL CHARACTERISTICS

**Sequential thermostatic shower mixer - Ref. H964015**

Connector	3/4"
Technology	SECURITHERM Securitouch sequential thermostatic mixer
Width	184mm
Flow rate	9 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	 
Warranty	