

SECURITHERM shower panel

Ref. 79239015

Thermostatic mechanical dual control


DESCRIPTION

SECURITHERM shower panel - Ref. 79239015

Dual control thermostatic shower panel:
 Anodised aluminium shower panel for wall-mounted, exposed installation.
 Top inlet via in-line stopcocks and conical Ø 15mm inlets.
 SECURITHERM thermostatic mixer.
 Adjustable temperature control from cold water to 41°C.
 Anti-scalding safety: automatic shut-off if cold or hot water supply fails.
 Anti-cold showers function: automatic shut-off if hot water fails.
 Thermal shocks are possible.
 1/4 turn non-time flow valves.
 Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation set at 6 lpm at 3 bar.
 Handset with removable flexible via rapid push-fit connector and wall-support supplied.
 Concealed fixings.
 Filters and non-return valves.
 Suitable for people with reduced mobility.
 30-year warranty.





TECHNICAL CHARACTERISTICS

SECURITHERM shower panel - Ref. 79239015

| | |
|---------------------|---|
| Connector | M½" Ø 15mm |
| Technology | Non-time flow |
| Height | 1050mm |
| Depth | 65mm |
| Width | 210mm |
| Flow rate | 6 lpm |
| Temperature limiter | Thermostatic |
| Finish | Aluminium |
| Norms | ACS |
| Warranty |  |



ADVANTAGES

-  Thermostatic control
-  Instant shut-off if cold water supply fails
-  Fixed shower head or handset
-  Aluminium body, brass controls

