

## SECURITHERM shower panel

Ref. 792410UK

Electronic battery-operated thermostatic




### DESCRIPTION

**SECURITHERM shower panel - Ref. 792410UK**





Electronic thermostatic shower panel:  
 Anodised aluminium shower panel for wall-mounted, exposed installation.  
 Concealed inlets via flexibles M $\frac{1}{2}$ ".  
 SECURITHERM thermostatic shower mixer.  
 Adjustable temperature control from cold water up to 38°C: 1st limiter set at 38°C, 2nd limiter set at 41°C.  
 Anti-scalding safety: immediate shut-off if cold or hot water supply fails.  
 Thermal shocks are possible.  
 Battery-operated with CR-P2 223 6V Lithium battery.  
 Infrared presence detection. Shower starts when hand is 4cm from the sensor.  
 Shuts off voluntarily or automatically after ~60 seconds.  
 Duty flush (~60 seconds every 24 hours after the last use).  
 Flow rate 6 lpm at 3 bar.  
 Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation.  
 Concealed fixings.  
 Filters and non-return valves.  
 Electronic shower panel suitable for people with reduced mobility.  
 30-year warranty.

### TECHNICAL CHARACTERISTICS

**SECURITHERM shower panel - Ref. 792410UK**

Supply	6V battery
Connector	M1/2"
Technology	Electronic
Height	1050mm
Depth	65mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	thermostatic
Finish	Aluminium
Warranty	

### ADVANTAGES

-  Total hygiene: operate without manual contact
-  Duty flush limits proliferation of bacteria
-  Thermostatic temperature regulation
-  Instant shut-off if cold water fails

