

SECURITHERM time flow shower panel

Ref. 79230415

Thermostatic time flow




DESCRIPTION

SECURITHERM time flow shower panel - Ref. 79230415





Thermostatic time flow shower panel:
 Large model satin stainless steel shower panel for wall mounted, exposed installation.
 Top inlet via in-line stopcocks and Ø 15mm conical inlets.
 SECURITHERM thermostatic shower mixer.
 Adjustable temperature control from cold water up to 41°C.
 Anti-scalding safety: automatic shut-off if cold or hot water supply fails.
 Thermal shocks are possible.
 Soft-touch operation.
 Time flow ~30 seconds.
 Flow rate 6 lpm at 3 bar.
 Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation.
 Integrated soap dish.
 Concealed fixings.
 Filters and non-return valves.
 Suitable for people with reduced mobility
 30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM time flow shower panel - Ref. 79230415

Connector	M½" Ø 15mm
Technology	Time flow
Height	1220mm
Depth	100mm
Width	250mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Stainless steel
Warranty	

ADVANTAGES

-  Thermostatic temperature regulation
-  Instant shut-off if cold water fails
-  80% water savings
-  Stainless steel panel, brass controls

