SECURITHERM time flow shower panel

Ref. 79230415

Thermostatic time flow

DESCRIPTION

SECURITHERM time flow shower panel - Ref. 79230415

Thermostatic time flow shower panel:
Large model satin stainless steel shower panel for wall mounted, exposed installation.
Top inlet via in-line stopcocks and Ø 15mm conical inlets.
SECURITHERM thermostatic shower mixer.
Adjustable temperature control from cold water up to 41°C.
Anti-scalding safety: automtaic shut-off if cold or hot water supply fails.
Thermal shocks are possible.
Soft-touch operation.
Time flow ~30 seconds.
Flow rate 6 lpm at 3 bar.
Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation.
Integrated soap dish.
Concealed fixings.
Filters and non-return valves.
Suitable for people with reduced mobility
30-year warranty.

ADVANTAGES

- Thermostatic temperature regulation
- Instant shut-off if cold water fails
- 80% water savings
- Stainless steel panel, brass controls

TECHNICAL CHARACTERISTICS

SECURITHERM time flow shower panel - Ref. 79230415

Connector	M½'' Ø 15mm
Technology	Time flow
Height	1220mm
Depth	100mm
Width	250mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Stainless steel
Warranty	30 YEAR WARRANTY