

KOMPACT washbasin and floor-standing WC combination

Ref. 160800

Satin finish 304 stainless steel, Wall mount, Floor mount central WC



DESCRIPTION

KOMPACT washbasin and floor-standing WC combination - Ref. 160800

Combination unit: washbasin and floor-standing central WC pan with recessed toilet roll holder.

Wall-mounted installation with 3 access panels, 2 on the sides and 1 on the top with theft prevention TORX security screws.

Bacteriostatic 304 stainless steel.

Polished satin finish.

Stainless steel unit thickness: 2mm.

Rounded corners and edges for improved safety.

Smooth surface for easy cleaning.

Suitable for prisons, police stations, etc.

WC pan is completely welded to washbasin, no screws: makes cleaning easier and prevents concealment of objects.

WC pan central to the unit.

Washbasin equipped with time flow tap: stainless steel tamperproof push-button and anti-blocking system, 7 second time flow, M1/2".

WC equipped with time flow flush valve, 7 second time flow, M3/4".

Water inlet: washbasin M1/2", WC M3/4".

Recessed horizontal water outlet: Ø 100mm.

Supplied with washbasin siphon.

Easy to install: only one water outlet for both washbasin and WC, water inlet and outlet already connected.

Weight: 36kg.

[Formerly ref: 0610030008]

TECHNICAL CHARACTERISTICS

KOMPACT washbasin and floor-standing WC combination - Ref. 160800

Height	1000mm
Length	400mm
Width	850mm
Thickness	2mm
Finish	304 polished satin stainless steel
Norms	ACS 
Warranty	

ADVANTAGES



Bacteriostatic 304 stainless steel



Suitable for secure sector

