

## SECURITHERM shower panel

Ref. 792320

Thermostatic time flow dual control


### DESCRIPTION

**SECURITHERM shower panel - Ref. 792320**

SECURITHERM dual control thermostatic time flow shower panel:  
 Anodised aluminium shower panel for wall-mounted, exposed installation.  
 With top inlet via in-line stopcocks, M $\frac{1}{2}$ ".  
 SECURITHERM thermostatic shower mixer.  
 Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.  
 Anti-scalding failsafe: automatic shut-off if cold water fails.  
 Anti-cold showers function: automatic shut-off if hot water fails.  
 Thermal shocks are possible.  
 Soft-touch operation.  
 Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation at 6 lpm at 3 bar.  
 Handset with removable flexible via push-fit rapid STOP connector and wall support supplied.  
 2x ~30-second time flow valves to control ROUND shower head and handset on flexible hose.  
 Concealed fixings.  
 Filters and non-return valves.  
 Shower panel suitable for people with reduced mobility.  
 30-year warranty.

### TECHNICAL CHARACTERISTICS

**SECURITHERM shower panel - Ref. 792320**

Connector	M1/2"
Technology	Time flow
Height	1050mm
Depth	65mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	thermostatic
Finish	Aluminium
Norms	ACS  
Warranty	



### ADVANTAGES



Thermostatic temperature regulation



Immediate shut-off if cold water fails



80% water savings



Aluminium body, brass controls

