SECURITHERM thermostatic sink mixer set

Ref. H9613

Sequential mixer and column set

DESCRIPTION

SECURITHERM thermostatic sink mixer set - Ref. H9613

SECURITHERM thermostatic sequential sink mixer set and column with retracting hand spray.

Ideal for baby baths.

Anti-scalding failsafe: shuts off automatically if cold or hot water supply fails.

Securitouch thermal insulation prevents burns.

Sequential: opens and closes with cold water.

No risk of cross flow between the hot and cold water.

No non-return valves on the inlets.

Swivelling column H. 195mm L. 215mm.

Retracting hand spray with 2 jet options: flow straightener/rain effect

Scale-resistant thermostatic sequential cartridge for single control temperature and flow-rate adjustment.

Temperature can be adjusted from cold water to 40°C with maximum temperature limiter set at 40°C.

Body and column with smooth interiors.

Flow rate regulated at 7 lpm.

No manual contact thanks to Hygiene control lever L. 100mm. Mixed water brass outlet L. 160mm.

BIOSAFE flexible shower hose reduces bacterial proliferation:

transparent polyurethane, smooth interior and exterior. Hose with narrow diameter (internal Ø 6mm): low water

volume. Specific counterweight.

PEX flexibles F3/8" and reinforced fixing via 2 stainless steel

Ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Suitable for people with reduced mobility.

30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM thermostatic sink mixer set - Ref. H9613

Connector	F3/8"
Technology	SECURITHERM sequential Securitouch
Drop height	195mm
Spout length	215mm
Flow rate	7 lpm
Temperature limiter	40°C





Sequential: opens/closes with cold water




Hygiene: no non-return valves



SECURITHERM: Optimal antiscalding safety



Sequential open and closing on cold water



DELABIE

Finish	Chrome-plated brass
Norms	ACS 🗓 🔘
Warranty	30 S WARRANTY
Repairability	50 g

© DELABIE https://www.delabie.co.uk